HUSTLER

COMBINING STYLE AND PROTECTION

Water-repellent, the blue flash polarised version repels heat, providing optimum protection and reducing glare. Ideal for off-shore activities. Also available in a smoke version.



31 a

SUPPLIED WITH

Microfibre pouch ETUIFS



- **+** SIDE SHIELDS
- **+** NON-SLIP BRIDGE
- **+** NON-SLIP TEMPLES



HUSTPOL

HUSTLER

COMBINING STYLE AND PROTECTION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
HUSTLER	Smoke	HUSTPSF	5-3,1 😭 1 FT C€	≅ EN166 FT C €	Anti-scratch/anti-fog
HUSILEN	Polarized Blue flash	HUSTFLASH	5-3,1 😭 1 FT C€	≅ EN166 FT C€	Anti-scratch/anti-fog
	Polarized	HUSTPOL	5-3,1 😭 1 FT C€		Anti-scratch/anti-fog

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- **F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

TECHNOLOGY

PPOLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment Filters 99 99% of LIVA/LIVB

PACKAGING AND EAN13 CODE						
	HUSTPSF	HUSTFLASH	HUSTPOL			
Individual plastic bag	3660740006594	3660740006600	3660740007348			
10 safety spectacles per inner box	3660740106591	3660740106607	36607400107345			
240 safety spectacles per outer pack	3660740206598	3660740206604	3660740207342			

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- **T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS				
LENSES	PC - 2,2 mm - Curve 8			
TEMPLES	Nylon + insert EVA			
STRAP	Non applicable			
FOAM	Non applicable			
SPARE LENSES	No			











01/10/2013

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

